



137.00 EUR
incl. 19% VAT, plus [shipping](#)

Support:  [Specifications \[EN\]](#)

- VIA VX800 Chipset
 - Support VIA C7 1.5GHz(90nm,FSB 400MHz,1.5GHz) processor
 - Integrated Chrome9 HC3 DX9 IGP
 - Integrated LVDS support 24-bit TFT LCD
 - Support 1 x 32-bit PCI slot
 - Support 2 x Serial ATA 2 Devices
 - Windows Vista Ready
 - Onboard Gigabit LAN
 - Support DC FAN
 - COM2 Support RS422/485
 - VIA VT1708B HD Audio Codec with 6-Channel
 - 170 x 170mm Mini-ITX Form Factor
 - Support Daughter board Expansion
 - Support Watch dog Technology
- | | |
|--------------------|--|
| 1. CPU | 1. Support VIA C7 1.5GHz(90nm,FSB 400MHz,1.5GHz) processor |
| | 2. Front Side Bus 400MHz |
| 1. Chipset | 1. VIA VX800 Chipsets |
| | 2. VIA Chrome9 HC3 IGP, 128Bit 3D engines(Share System Memory:64/128/256MB) |
| 1. Memory | 1. 1 * 240-pin DIMM Sockets for un-buffered DDR2 667MHz SDRAM up to 2GB |
| 1. Expansion Slots | 1. 1 * 32-bit PCI slots |

-
- | | |
|---------------------|--|
| 1. Power Management | 1. ACPI S3/S4 Compliant ,supports VIA PowerSaver™ feature |
| 1. Storage | 1. 2 * Serial ATA2 3Gb/s connectors with RAID 0,1 functions |
| | 2. 1 * Ultra DMA 133/100/66 IDE connector |
| 1. Audio | 1. VIA VT1708B HD Audio Codec with 6-Channel |
| 1. Ethernet LAN | 1. 1 * RTL8111C 10 / 100 / 1000 PCI LAN |
| 1. USB | 1. Embedded 6 * USB 2.0/1.1 |
| 1. LVDS | 1. Onboard 24-bit dual channel LVDS connector |
| | 2. |
| 1. Rear Panel I / O | 1. 2 * USB 2.0/1.1 ports |
| | 2. 1 * PS/2 connector for Keyboard and Mouse |
| | 3. 1 * RJ-45 ports |
| | 4. 3 * Audio I/O ports (Line-in, mic and line-out) |
| | 5. 1 * VGA port |
| | 6. 1 * DB-9 RS232 COM port |
| 1. Internal I / O | 1. 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports |
| | 2. 1 * CPU Smart Fan Connector, 2 * Sys/Chassis Fan Connectors |
| | 3. 3 * 9-Pin COM Port headers(COM2 Support RS422/RS485) |
| | 4. 1 * IR header |
| | 5. 1 * HDMI_SPDIF header |
| | 6. 1 * LVDS header |
| 1. BIOS | 1. Award 4MB SPI Flash ROM |
| 1. Form Factor | 1. Mini-ITX Embedded Motherboard(170mmx170mm) |
| 1. Temperature | 1. Operating within 0~60 centigrade |
| | 2. Storage within -20-85 centigrade |

Product Accessories

- COM cable
- Manual
- CD
- 1x SATA cable
- I/O shield
- 1x IDE cable