

179.00 EUR  
incl. 19% VAT, plus [shipping](#)



- INTEL® Pineview-D + NM10 Chipset
- Support INTEL®ATOM D525 Dual-Core (1.83GHz) CPU
- Supports 2 \* Gigabit LAN
- Integrated Realtek ALC662 HD Audio Code with 6-Channel
- Support Watch dog Technology
- Compliance with ERP standard
- Mini-ITX Form Factor(170mm x 170mm)
- Support Daughter board Expansion

|                        |                                                                                               |
|------------------------|-----------------------------------------------------------------------------------------------|
| <b>CPU</b>             | • INTEL ® Atom Dual-Core Processor D525 (45nm,1.80GHz,1024MB L2 Cache)                        |
| <b>Chipset</b>         | • INTEL®Atom D525 + NM10 chipset<br>• Build-in INTEL®GMA 3150 Graphics Core (DVMT Max. 384MB) |
| <b>Memory</b>          | • 2 * DDR3 800MHz Single CH SO-DIMM up to 4GB                                                 |
| <b>Expansion Slots</b> | • 1 * PCI slot<br>• 1 * Mini PCI-E socket                                                     |
| <b>Storage</b>         | • 4 * Serial ATA2 3Gb/s connectors support RAID 0, 1, JBOD<br>• 1 * IDE connector             |
| <b>Audio</b>           | • Realtek ALC662 HD Audio Code with 6-Channel                                                 |
| <b>Ethernet LAN</b>    | • Realtek RTL8111EVL PCI-E Gigabit Ethernet LAN                                               |

|                           |                                                                                                                                                                                                                                                                                                       |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| • <b>USB</b>              | <ul style="list-style-type: none"> <li>• Embedded 7 * USB 2.0/1.1</li> </ul>                                                                                                                                                                                                                          |
| • <b>Special Features</b> | <ul style="list-style-type: none"> <li>• Support ACPI S3</li> <li>• Support CPU Smart FAN &amp; DC FAN</li> </ul>                                                                                                                                                                                     |
| • <b>LVDS</b>             | <ul style="list-style-type: none"> <li>• Onboard 18-bit Single Channel LVDS connector</li> </ul>                                                                                                                                                                                                      |
| • <b>Rear Panel I/O</b>   | <ul style="list-style-type: none"> <li>• 4 * USB 2.0/1.1 ports</li> <li>• 1 * PS/2 KB/MS connector</li> <li>• 2 * RJ-45 port</li> <li>• 1 * Audio I/O port ( Line-in, MIC and Line-out )</li> <li>• 1 * VGA port</li> <li>• 1 * COM port</li> </ul>                                                   |
| • <b>Internal I/O</b>     | <ul style="list-style-type: none"> <li>• 3 * USB 2.0 ports</li> <li>• CPU / Chassis Fan connectors</li> <li>• 1 * 24-pin ATX Power connector</li> <li>• 1 * COM header ( COM2 for RS-232/422/485)</li> <li>• 1 * AUDIO_IN header</li> <li>• 1 * Parallel header</li> <li>• 1 * GPIO header</li> </ul> |
| • <b>BIOS</b>             | <ul style="list-style-type: none"> <li>• Award 8MB DIP-SPI Flash ROM</li> </ul>                                                                                                                                                                                                                       |
| • <b>Functional</b>       | <ul style="list-style-type: none"> <li>• ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Transportation, Financial Application</li> </ul>                                                                                                                         |
| • <b>Packing</b>          | <ul style="list-style-type: none"> <li>• Color Box Dimension ■ 200(W) x 200(D) x 70(H)mm</li> <li>• Cases Gross Weight ■ 15.4KGS</li> <li>• Cases Net Weight ■ 10.3KGS</li> <li>• 20 PCS / Cases, Case size : 720(L) x 410(W) x 200(H)mm</li> </ul>                                                   |
| • <b>Certificate</b>      | <ul style="list-style-type: none"> <li>• CE, FCC, RoHS</li> </ul>                                                                                                                                                                                                                                     |
| • <b>Temperature</b>      | <ul style="list-style-type: none"> <li>• Operating within 0~60 centigrade</li> <li>• Storage within -20-85 centigrade</li> </ul>                                                                                                                                                                      |
| • <b>Form Factor</b>      | <ul style="list-style-type: none"> <li>• Mini ITX Form Factor(170mmx170mm)</li> </ul>                                                                                                                                                                                                                 |