

469.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel® Skylake Celeron SoC Processor
- 1* 260-pin Dual-channel DDR4 2133MHz SODIMM Up to 16 GB
- 4* 10/100/1000 Base-TX Ethernet Ports
- 1* Full size Mini-SATA Socket (SATA + USB Signal)
- 2* Mini PCIe Slots (1* full size & 1* half size)
- 1* SIM card holder
- Supports on board TPM1.2/2.0 (option)
- 1* RS232 Console, 2* USB3.0, 2* USB2.0
- Supports Antenna up to 4

MB Model	– JNF731-XXXX / 3.5" SBC
Part No	– HBFDF731-3855-B (non-WIFI) / HBFDF731W-3855-B (WIFI) – HBFDF731-3955-B (non-WIFI) / HBFDF731W-3955-B (WIFI) – HBFDF731-3965-B (non-WIFI) / HBFDF731W-3965-B (WIFI)
Processor	– Intel® Skylake Celeron 3855U/3955U/3965U SoC Processor
Chipset	– SoC Integrated
Memory	– 1 * SO-DIMM DDR4-2133MHz up to 16GB

Storage	– 1 * 2.5" SATA3 6Gb/s internal drive bay (only support 2.5" HDD with a hight ≤ 10mm) – 1 * full size mSATA
Network	– 1 * Intel® i219LM GbE & 3 * Intel® i211AT (Default on board)
Expansion slot	– 1 * half size Mini PCIe slot (for WiFi expansion) – 1 * full size Mini PCIe slot with 1 * SIM card holder)
Front Panel I/O	– 1 * Power button, 1 * Reset button – 1 * Power LED, 1 * HDD LED – 2 * USB2.0 – 4 * NIC LED – 1 * COM & 1 * GPIO (option)
Rear Panel I/O	– 4 * RJ45 (3 * i211AT + 1 * i219LM) – 2 * USB3.0 – 1 * HDMI (Reserve, Max. resolution:4096 x 2304@24Hz) – 1 * RS232 – 1 * DC-in jack
Other Features	– TPM1.2 or TPM2.0 (On board option) – 0~255 segments by software programmable
Power Source	– FSP DC Adapter / AC 90~240V input / DC12V-5A-60W / LV6
Safety	– CE, FCC, LVD, RoHS
Temperature	– Operating Temperature: 0 ~ 50° C – Storage Temperature: -10 ~ 70° C
Dimensions	– 193 (W) x 142.4 (D) x 62 (H) mm
Packing	– Net Weight: 2.2KG – Gross Weight: 3.2KG – Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm
OS Support	– 32/64 bit versions of Windows 7, Windows 8.1, Windows 10, Linux
Warranty	– 2 Year limited warranty