

999.00 EUR
incl. 19% VAT, plus [shipping](#)



- Intel® Apollo Lake SoC Processor
- 1* DDR3L 1866MHz SODIMM up to 8 GB
- 4* USB3.1, 2* HDMI, 2* RJ45, 1* MIC/Line-out Combo, 1* COM (RJ45 type)
- Operating Temperature: -40 ~ 70° C
- M/B Form Factor : uTX (117x112mm)
- DC-12V_60W Adapter

MB Model	– MT95-90
Part No.	– HBFCT95-90B – HBFCT95W-90B (WIFI)
BIOS	– AMI Flash ROM
CPU/Chipset	– Intel® Apollo Lake SoC Processor (E3940 CPU TDP 9.5W)
Memory	– 1* DDR3L 1866MHz SO-DIMM up to 8 GB
Network	– 2* Intel® i210AT GbE
Storage	– 1* M.2 M-key (2242) Support SATA interface
Expansion	– 1* M.2 E-key (2230) Support USB2.0 & PCIe1 interface (for WiFi module installed) – 1* M.2 B-key (3042) Support USB3.0 interface (for 3G/4G/5G module installed)

Rear Panel I/O	– 2* USB3.1 (Gen1) – 2* HDMI (Max. Resolution: 3840 x 2160@30Hz) – 2* RJ45 – 1* MIC/Line-out Combo (Realtek® ALC662VD) – 1* COM (RJ45 type) – 2* Antenna holes (WiFi only) – 1* DC-in jack (Lockable type)
Front Panel I/O	– 1* Power button – 1* Power LED, 1* HDD LED, 2* LAN LED – 2* USB3.1 (Gen1) – 1* AT / ATX mode Switch
Power Source	– AC to DC Adapter / AC 90~240V_DC12V_5A_60W – MT95-90 MB_DC 12V input
Compliance	– CE, FCC, LVD, RoHS, ErP Ready
Temperature	– Operating Temperature: -40 ~ 70° C (Under the condition of using M.2 interface SSD) (The test environment is closed and windless) – Storage Temperature: -40 ~ 80° C – Humidity: 10% ~ 90% RH @40°C (non-condensing)
Dimensions	– 144 (W) x 116.9 (D) x 65 (H) mm
OS Support	– Windows 10, Linux