

598.00 EUR

incl. 19% VAT, plus [shipping](#)

- 9-36V DC-in !
- ARM Cortex RK3288 !
- Android 5.1/9.0, Debian 9.0 !
- IP65 Front !



- 10.1" 350 nits TFT LCD with LED backlight
- ARM Cortex RK3288 CPU, 4x 1,8 GHz
- Onboard 1333/2GB DDR3L DRAM
- Onboard 8G Flash ROM

- Support Android 5.1/9.0 or Debian 9.0
- Front IP65 for protection against water and dust
- Support 9-36V DC-in

Display	– IP65, NEMA 4 rugged protection, metal front bezel – 10.1" With LED Backlight – 350 nits Brightness (cd/m²) – 262K display color – 1280 x 800 @ 60Hz resolution – 160°/160° viewing angle (H/V) – 0.1695 x 0.1695mm pixel pitch – 16:10 aspect ratio – 600:1 contrast ratio – 25ms response time
Touch Screen	– Projected capacitive type – 257.10 x 159.66mm ±0.2mm active range – Transparency ■ 87% – Operating force ■ 80g – Surface Hardness ■ 6H (ASTM D3363, pressure 1N/45°)
Case	– Aluminum panel – Iron case – Black color – Spray paint coating requirement
Main System	– Rockchip® ARM Cortex A17 1.8GHz/QC processor – Onboard 1333/2GB DDR3L DRAM – Onboard 8G Flash ROM – Watchdog Timer 256 levels, 0~255 sec. – Speaker: 2* 2W/8Ohm – Camera: 1* 500W USB (Option) – OS Support Android 5.1/9.0 or Debian 9.0 – Power Consumption: 8.5W
Expansion	– 1* Micro SD socket
I/O Connector	– 2* USB2.0 (USB1 Co-lay OTG) – 1* HDMI 1.4 – 1* AUDIO(Line-out +MIC) – 1* Micro SD Socket – 1* Power Button – 1* GbE – 1* 9~36V DC jack
Power Input	– 9~36V DC-in
Dimensions	– 259.3 * 177.3 * 39.0mm
Compliance	– CE, FCC, IP65(Front)-Option
Safety	– Shock: 15G, 11ms duration – Vibration: 5~500Hz/1 Grms
Temperature	– Operating: -10°C ~ 50°C – Storage: -20°C ~ 60°C