



49.95 EUR

incl. 19% VAT, plus [shipping](#)

- MediaTek Chip !
- LED indicator for GPS fix !

- High sensitivity MediaTek chipset (Tracking sensitivity: -165 dBm)
- Extremely fast TTFF (Time To First Fix) at low signal levels
- Supports NMEA 0183 data protocol
- Built-in backup power to reserve system data for fast satellite acquisition
- Built-in patch antenna
- Super-strong magnet for attaching to the car
- Water-repellent and non-slip on the bottom
- USB interface connector
- LED indicator for GPS fix or not fix

->LED OFF: Receiver switched off

->LED ON: No fixed network, signal search

->LED flashes: Position fixed

General	
Chipset	MediaTek AG3335MN
Frequency	GPS, Galileo, QZSS, SBAS : L1, 1575.42 MHz C/A code GLONASS : L1, 1602 MHz BeiDou : B1, 1561.098 MHz
C/A code	1.023 MHz chip rate
Channels	75 track verification channels
Sensitivity	Tracking: -165 dBm
Accuracy	
Accuracy	3 meters, 2D RMS 2.5 meters, 2D RMS, SBAS enabled
Velocity	3 meters, 2D RMS 2.5 meters, 2D RMS, SBAS enabled
Time	1us synchronized to GPS time
Datum	
Default	WGS-84

Acquisition Time	
Reacquisition	0.1 sec., average
Hot start	< 1 sec., average
Cold start	< 33 sec < 15 sec with AGPS
Dynamic Conditions	
Altitude	18,000 meters (60,000 feet) max
Velocity	515 meters /second (1000 knots) max
Acceleration	Less than 4g
Jerk	20m/sec
Power	
Main power input	4.5V ~ 6.5V DC input
Power consumption	42mA @5V
Protocol	
Electrical level	Output voltage level: 0V ~ 2.85V
Baud rate	4800 bps, 8 data bits, no parity, 1 stop bit
Output message	NMEA 0183 GGA, GSA, GSV, RMC GLL, VTG, ZDA, GRS, GST
Physical Characteristics	
Dimension	53mm diameter, 19.2mm height
Cable Length	1.5M
Operating temperature	-40■ to +85■