

198.00 EUR  
 incl. 19% VAT, plus [shipping](#)

- Pico-ITX
- SATA
- DDR-II !
- 1 Ghz CPU



<b>Model</b>	VIA EPIA PX1000G
<b>Processor</b>	VIA C7 1.0 GHz - Socket Nano25G4
<b>Chipset</b>	VIA V3700 Unified Digital Media GSP Chipset
<b>System Memory</b>	1 DDR2 512 3200MHz module Up to 1GB memory size
<b>GPU</b>	Integrated VIA UniChrome Pro3 3200G GSP graphics with MPEG-2/4 and WMV9 decoding acceleration

Onboard IDE	1 SATA/IDE 133/100MHz connector (2.0mm 44-pin header)
Onboard Serial ATA	1 SATA connector
Onboard LAN	1 VIA VT6102G 10/100Mbps Ethernet controller  with Power Managemen System
Onboard Audio	VIA VT1708A High Definition Audio Codec
Internal I/O Connectors	<p>4 USB pin headers for 4 USB 2.0 ports</p> <ul style="list-style-type: none"> <li>• 1 COM port connector</li> <li>• 1 PS2 mouse/keyboard pin header</li> <li>• 1 LVDS/DVI connector</li> <li>• 1 Multimedia connector to support external TV-out interface, Video capture port interface and Low pin count interface</li> <li>• 1 Audio pin header for line-out, line-in, mic-in, S/PDIF in, and 7.1 channels audio output</li> <li>• 1 Fan pin header for CPU fan</li> <li>• 1 Pico-ITX power connector</li> </ul>
External I/O Ports	<p>1 RJ-45 LAN port</p> <ul style="list-style-type: none"> <li>• 1 VGA port</li> </ul>
BIOS	<p>Award BIOS</p> <ul style="list-style-type: none"> <li>• 4/8Mbit flash memory</li> </ul>
Management	<p>CPU temperature reading (manufacturing option)</p> <ul style="list-style-type: none"> <li>• Watch Dog Timer (manufacturing option)</li> <li>• Keyboard-Power-on, Timer-Power-on</li> <li>• Wake-on-LAN</li> <li>• System power management</li> <li>• AC power failure recovery</li> </ul>
Operating Temperature	0°C - 50°C
Operating Humidity	0% - 95% (relative humidity, non-condensing)
Form Factor	• Pico-ITX 10 cm x 7.2 cm